



TIGER Series

www.kacer.com

Front and Back I/O output design; Super Excellent heat-dissipating feature, COM, USB, DI, DO for expansion

Optional Accessory :
• Wall Mount kit

Application :
Automation control / POS / IP PoE Surveillance / Car PC



| Technical Data : | |
|--------------------------|---|
| • Dimension | 58.8H x 190.8W x 130D mm 59.4H x 190.8W x 195D mm - 3I770A |
| • Material | Aluminum |
| • Color | Black |
| • VESA Mounting (option) | 75 x 75 mm |
| • Weight | 1.2Kg (Incl. M/B) 2.5Kg (Incl. M/B) - 3I770A |
| • Storage Space | mSATA / 2.5" HDD |

M/B information: (Please refer to M/B specification)



| CPU Type | M/B Model | VGA | COM | LAN | USB | Audio | DVI / HDMI | Others | Operation Temp | |
|-------------------|-------------------------|-----|-----|-------------|-----|-------------------|------------|---|----------------|--------------------|
| | | | | | | | | | HDD | mSATA (Industrial) |
| Intel® Bay-Trail | 3I380NX | 1 | 3 | 3 | 3 | Option | HDMI | DI / DO / SIM Card Socket / Micro SD Socket | 50°C | 60°C |
| | 3I380A | 1 | 4 | 2 | 4 | Line out / Mic-in | HDMI | DI / DO (Option) | 50°C | 60°C |
| Intel® Ivy Bridge | 1047 UE 1.4GHz,i3,i7 | 1 | 3 | 2 | 4 | Line out / Mic-in | DVI & HDMI | DI / DO | 50°C | 60°C |
| | | | 6 | | | | | | | |
| | 3I847AW | 1 | 2 | 1 + 4 x PoE | 3 | Line out / Mic-in | HDMI | DI / DO | 50°C | 60°C |
| | 3I770A | 1 | 6 | 2 | 4 | Line out / Mic-in | HDMI | DI / DO (Option) | 50°C | 60°C |

| More Functions | | | | |
|----------------|-------|-----|---------|-----|
| 3G / 4G | Wi-Fi | GPS | 6 x COM | DIO |

The above available functions outline the possibility with system, for more information please contact us.

Dimension

