IMBA-C2260-i2-R11

ATX motherboard supports 22nm LGA1150 Intel® Xeon E3, Core™ i3, Pentium® and Celeron®, DDR3, VGA, dual Intel® PCIe GbE, USB 3.0, SATA 6Gb/s, iRIS-2400 and RoHS



Fully Jumper-less Support





IPMI 2.0 Compliant | One Key Recovery | Native PCIe Gen.3

DDR3 1600 | Jumper-less | USB 3.0 | SATA 6Gb/s | PCIe GbE | mSATA

Specifications

- CPU
  LGA1150 Intel® Xeon® E3, Core™ i3, Pentium® or Celeron® processor supported
- Chipset
  Intel® C226
- Memory
  Four 240-pin 1600/1333 MHz dual-channel DDR3 & DDR3L SDRAM ECC and non-ECC unbuffered DIMMs support up to 32 GB
- BIOS
  UEFI BIOS
- Ethernet
  LAN1: Intel® I217LM with Intel® AMT 9.0 support
  LAN2: Intel® I210-AT PCIe controller with NCSI support
- Graphics Engine
  Intel® HD Graphics Gen 7.5 supports DX11.1 and OpenCL 1.2, OpenGL 3.2
  Full MPEG2, VC1, AVC Decode
- Display Output
  1 x VGA (up to 1920x1200@60 Hz)
  1 x iDP interface for HDMI, LVDS, VGA, DVI, DP (up to 3840x2160@60 Hz)
- Audio
  Realtek ALC662 HD codec supports 5.1-channel
  3 x Audio jacks (line-out, line-in, mic-in) on rear IO
  1 x Front audio (2x5 pin)
- External I/O Interface
  1 x KB/MS — 4 x USB 2.0
  1 x RS-232 — 4 x USB 3.0
- Internal I/O Interface
  1 x KB/MS (1x6 pin) — 1 x RS-422/485 (1x4 pin, P=2.0)
  1 x LPT (2x13 pin, P=2.54) — 4 x RS-232 (2x20 pin, P=2.54)
  1 x mSATA (colay SATA 6) — 4 x USB 2.0 (2x4 pin,P=2.54)
  6 x SATA 6Gb/s (RAID 0/1/5/10 supported)
- Front Panel
  1 x Front panel (2x7 pin, power LED, HDD LED, speaker, power button, reset button)
- LAN LED
  2 x LAN LED (1x2 pin)
- TPM
  1 x TPM (2x10 pin)
- SMBus
  1 x SMBus (1x4 pin)
- I²C
  1 x I²C (1x4 pin)
- iRIS Remote Management Module: 1 x iRIS-2400 slot
- Expansion
  1 x PCIe x16 slot
  3 x PCIe x4 slot (support PCIe x1)
  Default setting: 1 x PCIe x8 Gen 3 + 2 x PCIe x4 Gen 3 signal
  Optional setting: 1 x PCIe x16 Gen 3 by BIOS setting
  1 x PCIe x1 slot
  2 x PCI slot
- Watchdog Timer: Software programmable, support 1~255 sec. system reset
- Digital I/O: 8-bit digital I/O (2x5 pin)
- Fan Connector
  1 x CPU fan (1x4 pin)
  2 x System fan (1x3 pin)
- Power Supply: ATX power supply
- Power Consumption
  3.3V@0.57A, 5V@4.50A, 12V@0.14A, Vcore_12V@5.20A, 5VSB@0.19A
  (Intel® E3-1240 v3 3.4GHz CPU with 16 GB (4x4 GB) 1333 MHz DDR3 memory)
- Operating Temperature: -20°C ~ 60°C
- Storage Temperature: -30°C ~ 70°C
- Operating Humidity: 5% ~ 95%, non-condensing
- Dimensions: 244mm x 305mm
- Weight: GW: 1200g / NW: 700g

Features

1. LGA1150 Intel® Xeon® E3/Core™ i3/Pentium®/Celeron® processor supported
2. Dual-channel DDR3 1600/1333 MHz support up to 32 GB
3. Intel® PCIe GbE with Intel® AMT 9.0 support
4. Support PCI Express generation 3.0 at 8GT/s I/O bandwidth
5. USB 3.0, SATA 6Gb/s and mSATA supported
6. High-speed interface for one PCIe x8 or two PCIe x4 add-on cards
7. IEI jumper-less function
8. IEI One Key Recovery solution allows you to create rapid OS backup and recovery
9. Support IPMI 2.0 via iRIS-2400 module

Packing List

1 x IMBA-C2260-i2 single board computer	
1 x I/O shielding	1 x Utility CD
2 x SATA cable	1 x QIG

Ordering Information

Part No.	Description
IMBA-C2260-i2-R11	ATX motherboard supports 22nm LGA1150 Intel® Xeon E3, Core™ i3, Pentium® and Celeron® per Intel® C226, DDR3, VGA, Dual Intel® PCIe GbE, four USB 3.0, six SATA 6Gb/s, HD Audio, iRIS-2400 and RoHS
iRIS-2400-R10	IPMI 2.0 adapter card with AST2400 BMC chip for DDR3 SO-DIMM socket interface
19800-000049-RS	LPT flat cable, 240mm, P=2.54
19800-000075-RS	PS/2 KB/MS cable with bracket, 220mm, P=2.0
19800-003100-300-RS	Dual port USB cable with bracket, 300mm, P=2.54
19800-010500-200-RS	USB 3.0 cable 457mm with bracket
32102-000100-200-RS	SATA power cable, MOLEX 5264-4P to SATA15P
32205-001203-200-RS	RS-232 cable, 40-pin to four DB-9, 400mm, P=2.54
32205-003800-300-RS	RS-422/485 cable, 200mm, P=2.0
CF-1156A-RS-R11	High performance LGA1155/LGA1156 cooler kit, 1U chassis compatible, 73W
CF-1156E-R11	High performance LGA1155/LGA1156 cooler kit, 95W
DP-DP-R10	DisplayPort to DisplayPort converter board (for IEI iDP connector)
DP-DVI-R10	DisplayPort to DVI-D converter board (for IEI iDP connector)
DP-HDMI-R10	DisplayPort to HDMI converter board (for IEI iDP connector)
DP-LVDS-R10	DisplayPort to 24-bit dual-channel LVDS converter board (for IEI iDP connector)
DP-VGA-R10	DisplayPort to VGA converter board (for IEI iDP connector)
TPM-IN01-R20	20-pin Infineon TPM module, software management tool, firmware v3.17